



Solar Street Light

ML-5000-1230-201/07

SOLAR STREET LIGHT


Mutian solar street light features an integrated battery enclosure and your choice of luminaire. A specially designed solar pole meets wind loads and the luminaire. The system is configured according to your location and lighting requirements to run throughout the night.

WHY SOLAR?

- **REMOTE LOCATIONS**
Where grid is difficult to access
- **IMMEDIATE ENERGY SAVINGS**
No energy costs throughout life of product
- **LOWER INSTALLATION COSTS**
No trenching or cabling
Shorter installation time compared to on grid systems

OUR DIFFERENCE

- **INDUSTRY-LEADING EXPERTISE**
Field leader in solar LED lighting solutions, since 2006
- **ADVANCED LIGHTING TECHNOLOGY**
Designed for lighting applications
- **CUSTOM SOLUTION FOR YOUR APPLICATION**
Precision-engineered for your application



Mutian Solar Energy Sciencetech Company

No. 5699, North Second Ring Road, Baoding, China

www.solararmt.com | Tel: +86-312-3917316 | Fax: +86-312-3917315 | Email: sales@solararmt.com

Solar Street Light Parameter

Product name	Solar Street light	
Model No.	ML5000-1230-201/07	
Performance	Lighting time per day	12hours (4h full power mode+8h half dimming mode)
	Autonomy days	3 days
Solar Modules	Power (Wp)	100Wp (17.2V100Wp× 1pc)
	Type	Poly crystalline silicon
	Dimension	11610mm/670mm/30mm
	Weight	8.6kg
Light Luminaire	Material	Aluminum die casting & Toughened glass
	Operating Temperature	-40°C~75°C
	Power	30W
	Lumens	3600 Lm
	LED Chip	Bridgelux LED chips with high brightness, or customized
	Color Temperature	4000-7000K(warm white/pure white/cold white)
	Operating temperature	-40°C~70°C
Lighting Pole	Height	6m
	Material	Q235
	Surface Treatment	Hot-dip galvanizing, Static spray for led solar street light
Battery	Capacity	120AH (12V120AH× 1pc)
	Type	Gel/Lead-acid Battery
	Dimension	406mm/174mm/208mm
	Weight	33.4kg
Controller	Rated voltage and current	12V/10A
	Weight	0.165Kg
	Control mode	Light control + time control
	IP level	IP67
	Protective Function	overcharging, discharging, voltage surge, reverse polarity, etc.
Accessories	Cable	2.5mm ² 13m
	Battery Box	120AH waterproof ABS battery box 1 pc
	Foundation Kit	Dismountable foundation kit, saving in shipping

Mutian Solar Energy Sciencetech Company

No. 5699, North Second Ring Road, Baoding, China

www.solarmt.com | Tel: +86-312-3917316 | Fax: +86-312-3917315 | Email: sales@solarmt.com

Product Details



Solar Modules



Light Luminaire



Controller



Battery and Box

Easy Installation



Mutian Solar Energy Sciencetech Company

No. 5699, North Second Ring Road, Baoding, China

www.solarmt.com | Tel: +86-312-3917316 | Fax: +86-312-3917315 | Email: sales@solarmt.com